



## Data Sheet and Installation Manual

### Model OAS-3L/OAS-2L Driver Hydration Systems

#### Description

The Oasis™ Models OAS-3L and OAS-2L help keep you as a driver hydrated in the extreme conditions found in driving a race car. An insulated soft container helps to keep liquids cool so the internal cooling rate is maximized. A 90° bite valve is connected to a 69” drinking tube to maximize mounting location, comfort and accessibility by the driver.

The Oasis™ Models OAS-3L and OAS-2L includes a light weight silver powder coated mounting plate and is designed to be mounted in a variety of locations and positions. A wide screw type cap allows for easy and fast filling and emptying.



OAS-3L

#### Features

Available in 3 or 2 Liter  
Insulated

Light weight  
Designed for Personal Use

69” Extended Tubing  
Easy Installation

#### Specifications

Capacities: 3 liter & 2 liter  
Tube Length: 69 inches  
Dimensions: 20.0”H x 6.75”W x 4.0”D  
(50.8 x 12.0 x 10.2 cm)  
Weight: 2.75 lbs (1.25 kg)

#### Installation

Carefully choose the mounting location and measure to ensure that the extended drinking tube is accessible and comfortable during use. Using the slots at the top of the mounting plate, install and secure the Oasis™ mounting plate with wire ties or some other flexible attachment method. The liquid container can be hung on the mounting tabs and then secured to the mounting plate using wire ties.

#### Ordering Information

OAS-3L 3 Liter Hydration System OAS-2L 2 Liter Hydration System

#### Related Products

OAS-KIT Oasis™ Driver Hydration System Cleaning Kit